

PanelView Standard 600 Terminals Primary Replacement Options (Continued)

PanelView Standard Terminals						PanelView Plus 7 Terminals – Primary Replacement Options						
Model	Cat. No.	Panel Cutout Dimensions		Display Resolution	Comm.	Cat. No.	Panel Cutout Dimensions		Display Resolution	Comm.	Adapter Plate Cat. No.	Notes
		Height mm (in.)	Width mm (in.)				Height mm (in.)	Width mm (in.)				
600	2711-B6C15	167 (6.57)	264 (10.39)	320 x 234	ControlNet	2711P-B7C22A9P	142 (5.59)	237 (9.33)	640 x 480	Dual Ethernet ports	2711P-RAAK7	PanelView Plus 7 Performance 6.5-in. terminal benefits: • Higher resolution • DLR Communication = Ethernet. Operator input = keypad and touch. Power input = AC or DC. ⁽¹⁾ Conformal coat = No. Adapter plate is necessary for drop-in replacement.
					2711P-B7C22D9P							
	DH-485				2711P-B7C22A9P							
					2711P-B7C22D9P							
					2711P-B7C22A9P							
					2711P-B7C22D9P							
	RS-232 (DH-485)				2711P-B7C22A9P							
					2711P-B7C22D9P							
					2711P-B7C22A9P							
					2711P-B7C22D9P							
	DH+				2711P-B7C22A9P							
					2711P-B7C22D9P							
	EtherNet/IP				2711P-B7C22A9P							
					2711P-B7C22D9P							
	2711-T6C1L1	125 (4.91)	158 (6.20)	320 x 234	Remote I/O	2711P-T6C21D8S	123 (4.84)	156 (6.14)	640 x 480	One Ethernet port	N/A	PanelView Plus 7 Standard 6-in. terminal benefits: Higher resolution Application limits: • Max. screen count: 25 • Max. alarm messages: 200 • Max. number of controllers: 1 Communication = Ethernet (dual Ethernet ports are available). Operator input = only touch. Power input = only DC. Conformal coat = No.
	DeviceNet											
	RS-232											
	RS-232 (DF1)											
	ControlNet											
	DH-485											
	RS-232 (DH-485)											
	DH+											
	EtherNet/IP											

⁽¹⁾ AC power is only available on Series A terminals. DC power is only available on Series B terminals.

PanelView Standard 600 Terminals Secondary Replacement Options

PanelView Standard Terminals						PanelView Plus 7 Terminals – Secondary Replacement Options						
Model	Cat. No.	Panel Cutout Dimensions		Display Resolution	Comm.	Cat. No.	Panel Cutout Dimensions		Display Resolution	Comm.	Adapter Plate Cat. No.	Notes
		Height mm (in.)	Width mm (in.)				Height mm (in.)	Width mm (in.)				
600	2711-K6C1	167 (6.57)	264 (10.39)	320 x 234	Remote I/O	2711P-T7C21D8S	142 (5.59)	184 (7.24)	640 x 480	One Ethernet port	N/A	PanelView Plus 7 Standard 6.5-in. terminal benefits: Higher resolution Application limits: • Max. screen count: 25 • Max. alarm messages: 200 • Max. number of controllers: 1 Communication = Ethernet (dual Ethernet ports are available). Operator input = only touch. Power input = only DC. Conformal coat = No.
	2711-K6C1L1				DeviceNet							
	2711-K6C10											
	2711-K6C10L1											
	2711-K6C14											
	2711-K6C14L1											
	2711-K6C12				RS-232							
	2711-K6C12L1				RS-232 (DF1)							
	2711-K6C16											
	2711-K6C16L1				ControlNet							
	2711-K6C15											
	2711-K6C15L1				DH-485							
	2711-K6C2											
	2711-K6C2L1											
	2711-K6C3											
	2711-K6C3L1											
	2711-K6C5				RS-232 (DH-485)							
	2711-K6C5L1											
	2711-K6C9				DH+							
	2711-K6C9L1											
	2711-K6C8											
	2711-K6C8L1											
	2711-K6C20				EtherNet/IP							
	2711-K6C20L1											
	2711-B6C1				Remote I/O							
	2711-B6C1L1											
	2711-B6C10				DeviceNet							
	2711-B6C10L1											
	2711-B6C14											
	2711-B6C14L1											
	2711-B6C12				RS-232							
	2711-B6C12L1											
	2711-B6C16				RS-232 (DF1)							
	2711-B6C16L1											

PanelView Standard 600 Terminals Secondary Replacement Options (Continued)

PanelView Standard Terminals						PanelView Plus 7 Terminals – Secondary Replacement Options						
Model	Cat. No.	Panel Cutout Dimensions		Display Resolution	Comm.	Cat. No.	Panel Cutout Dimensions		Display Resolution	Comm.	Adapter Plate Cat. No.	Notes
		Height mm (in.)	Width mm (in.)				Height mm (in.)	Width mm (in.)				
600	2711-B6C15	167 (6.57)	264 (10.39)	320 x 234	ControlNet	2711P-T7C21D85	142 (5.59)	184 (7.24)	640 x 480	One Ethernet port	N/A	PanelView Plus 7 Standard 6.5-in. terminal benefits: Higher resolution Application limits: • Max. screen count: 25 • Max. alarm messages: 200 • Max. number of controllers: 1 Communication = Ethernet (dual Ethernet ports are available). Operator input = only touch. Power input = only DC. Conformal coat = No.
	2711-B6C15L1											
	2711-B6C2											
	2711-B6C2L1											
	2711-B6C3											
	2711-B6C3L1											
	2711-B6C5											
	2711-B6C5L1											
	2711-B6C9											
	2711-B6C9L1											
	2711-B6C8											
	2711-B6C8L1											
	2711-B6C20											
	2711-B6C20L1											
	2711-B6C20L1											
	2711-T6C1L1	125 (4.91)	158 (6.20)	320 x 234	Remote I/O	2711P-T7C22D9P	142 (5.59)	184 (7.24)	640 x 480	Dual Ethernet ports	N/A	PanelView Plus 7 Performance 6.5-in. terminal benefits: • Higher resolution • DLR Communication = Ethernet. Operator input = only touch. Power input = only DC. Conformal coat ⁽¹⁾ Adapter plate is necessary for drop-in replacement.
	2711-T6C10L1											
	2711-T6C14L1											
	2711-T6C12L1											
	2711-T6C16L1											
	2711-T6C15L1											
	2711-T6C2L1											
	2711-T6C3L1											
	2711-T6C5L1											
	2711-T6C9L1											
	2711-T6C8L1											
2711-T6C20L1												
2711-T6C20L1												
2711-T6C20L1												

⁽¹⁾ Conformal coating is available for the DC power, touch models (and the 15-in. DC power combination keypad/touch model) of the PanelView Plus 7 Performance family. To order a terminal that is conformal-coated, add K to the end of a DC-power catalog number; for example, 2711P-T7C22D9PK.